

EUROMASK®

HIGH TEMPERATURE TAPE CLT

Features :

CLT is a 90µ PET film with 40µ high performance clear silicone adhesive. Suitable for all high temperature masking process.

- 204°C resistant
- Powder Coating and Anodizing applications
- Clean removal, no adhesive residue



Technical Data :

Carrier		PET	
Adhesive		Silicone	
Carrier Thickness (mm)	ASTM D 1000	0.05	± 0,003
Total Thickness (mm)	ASTM D 1000	0.09	± 0,005
Adhesion to Steel (N/25mm – g/25mm)	ASTM D 1000	9.8 – 1000	± 2,5 - ± 232
Tensile Strength (N/25mm – kg/25mm)	ASTM D 1000	196 – 20	± 20 - ± 5
Elongation (%)	ASTM D 1000	100	± 22
Dielectric Strength (kV)	ASTM D 149	7.0	
Class of Insulation (°C)	UL 510	B / 130 UL	
Temperature Range (°C)	For 60'	-51 to +204	
Tape Length (m)		66	

NOTE: our recommendations are made in good faith and are based on our experience with this product. Since the conditions of use of this product are beyond our control, this data is given on the express condition and understanding that Finishing Group s.r.l. will not be liable to any person by reason thereof. Nothing herein shall be deemed to be a recommendation to use any product in violation of any existing patent right.