

EUROMASK®

HIGH TEMPERATURE TAPE STC

Features :

CLT is a 60µ PET tape with 40µ clear silicone high performance adhesive.

- Useful for Powder coating and anodizing applications.
- Indicate to curve surfaces.
- Clean removal, no adhesive residual



Technical Data :

Carrier

PET film

Adhesive

Silicon

Carrier Thickness (mm)

ASTM D 1000

0.025 ± 0,003

Total Thickness (mm)

ASTM D 1000

0.062 ± 0,005

Adhesion to Steel (N/25mm – g/25mm)

ASTM D 1000

7.4 – 750 ± 1,5-150

Tensile Strength (N/25mm – kg/25mm)

ASTM D 1000

108 – 11 ± 20 - 2

Elongation (%)

ASTM D 1000

100 ± 23

Dielectric Strength (kV)

ASTM D 149

5.5 ±0,5

Class of Insulation (°C)

UL 510

B / 130 UL

Temperature Range (°C)

For 60'

-51 to +177

Tape Length (m)

66

NOTE: our recommendations are made in good faith and are based on our experience with this product. Since the conditions of use of this product are beyond our control, this data is given on the express condition and understanding that Finishing Group s.r.l. will not be liable to any person by reason thereof. Nothing herein shall be deemed to be a recommendation to use any product in violation of any existing patent right.